

DECLARATION OF PERFORMANCE		Nr : 02/XGGKTOP30/03
According to the regulation 305/2011/EU		
AUSTROTHERM XPS® TOP 30 SF		
1. Identification code of the product type:	XPS-EN 13164-T1-DS(70,90)-CS(10\Y)300-DLT(2)5-CC(2/1,5/50)130-WD(V)3*-WL(T)0,7-FTCD1	* The classification of water absorption by diffusion depends on thickness.
2. Intended use:	Thermal insulation for buildings	
3. Manufacturer:	Austrotherm GmbH Friedrich Schimid-Straße 165, A-2754 Wopfing	
4. Authorised representative:	NPD	
5. System AVCP:	305/2011/EU insert V., system 3.	
6a. Harmonized standard: of the Notified Body:	MSZ EN 13164:2012+A1:2015 FIW (NB 0751)	
6b. European enquiry document:	NPD	

7. Performance according to the declaration:		
Essential characteristics - (EN13164-ZA1)	Symbols	Performance
Thickness tolerance	d_N	T1
Thermal conductivity	λ_D	W/mK
30mm		0,033
40-50mm		0,032
60mm		0,033
70-120mm		0,035
140-160mm		0,036
Heat conduction resistance (see table below)	R_D	m ² K/W
Compressive strength (for 10% compression)	CS(10\Y)	300
Tensile strength perpendicular to plane	TR	NPD
Reaction to fire	Class	E
Glow (Annealing)		(a)
Long-term water uptake	WL(T)	0,7
Vapor diffusion water uptake	WD(V)	3
Vapor diffusion resistance number	MU	100
Creep	CC (2/1,5/50)	130
Change in flammability properties due to heat, weather or ageing	(b), (c)	
Change in thermal conductivity due to heat, weather or ageing	see λ_D and R_D	
Freeze-thaw resistance after vapor diffusion water absorption	FTCD	1
Freeze-thaw resistance after full immersion in water	NPD	
Dimensional stability at normal climate	DS	(70,90)
Deformation at a given pressure and temperature	DLT	(2)5
Hazardous materials	The product does not contain hazardous materials	
8. In conformity with technical documentation or specific technical documentation	NPD	
9. Other information	availability: www.austrotherm.hu/teljesitmenynyilatkozatok Production date and other information can be found on the packaging.	

The performance of the product identified in points 1 is conformity with the declared performances. The 305/2011/EU declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

This product does not contain HBCD

Signed for and on behalf of the manufacturer by:

Mag. Klaus Haberfellner,
general manager

Wopfing, januar 2019.



(name and title)	(place and date)	(signature)
------------------	------------------	-------------

Thickness (mm)	Heat conduction resistance R_D (m ² K/W)	Thickness (mm)	Heat conduction resistance R_D (m ² K/W)	Thickness (mm)	Heat conduction resistance R_D (m ² K/W)
30	0,90	70	2,00	140	3,85
40	1,20	80	2,25	160	4,40
50	1,55	100	2,85		
60	1,80	120	3,40		

(a) the test procedure is currently being developed

(b) the properties do not change in the case of fire

(c) the fire resistance of the product does not deteriorate over time

